SAFETY DATA SHEET

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier

Product Name White Cream Hardener

Recommended Use of the Chemical and Restrictions on Use
Recommended Use Polymer Reaction Catalyst

Details of the Supplier of the Safety Data Sheet

Supplier's details

Quality Hardener A division of DBF, Inc. 18576 Krause PO Box 2385 Riverview, MI 48193

Phone: 734-285-1480

24 Hour Emergency Telephone Number Chemtrec 800-424-9300

2. HAZARDS IDENTIFICATION

Classification

Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2A
Skin sensitization	Category 1
Acute aquatic toxicity	Category 1
Organic peroxides	Type E



Signal Word WARNING

Hazard Statements

Heating may cause a fire
Very toxic to aquatic life
Causes serious eye irritation.
Causes skin irritation.
May cause an allergic skin reaction

Precautionary Statements - Prevention

Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep away from clothing, incompatible materials and combustible materials. Keep only in original container. Avoid breathing dust. Wash hands thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.

Precautionary Statements - Response

IF ON SKIN: Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

Precautionary Statements - Storage

Protect from sunlight. Store at temperatures not exceeding 25 °C/77 °F. Keep cool. Store away from other materials.

Precautionary Statements - Disposal

Dispose of contents/container in accordance with all local, regional, national and international regulations.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Dibenzoyl peroxide	94-36-0	≥50 to <u><</u> 75
Zinc Stearate	557-05-1	<u><</u> 10
Calcium Sulfate	7778-18-9	<u><</u> 5

4. FIRST AID MEASURES

First Aid Measures

General Advice Provide this SDS to medical personnel for treatment. Get Medical advice/attention if you feel

unwell.

Eye Contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

Skin Contact IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get

medical advice/attention. Remove contaminated clothing and shoes.

Inhalation IF INHALED: Call a POISON Center or doctor if you feel unwell.

Ingestion Do NOT induce vomiting. IF SWALLOWED: Call a POISON CENTER or doctor if you feel

unwell.

Most Important Symptoms and Effects, both Acute and Delayed

Potential acute health effects

Eye contact Causes serious eye irritation.

Inhalation No known significant effects or critical hazards.

Skin contact Causes skin irritation. May cause an allergic skin reaction.

Ingestion No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact Adverse symptoms may include pain or irritation, watering, redness.

Inhalation No specific data.

Skin contact Adverse symptoms may include irritation, redness.

Ingestion No specific data.

Indication of any Immediate Medical Attention and Special Treatment Needed, if necessary

Note to Physicians In case of inhalation of decomposition products in a fire, symptoms may be delayed.

The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments No specific treatment.

Protection of first-aiders

No action shall be taken involving any personal risk or without suitable training. It may be

dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

5. FIRE-FIGHTING MEASURES

Extinguishing media

Unsuitable Extinguishing Media None known.

Specific Hazards Arising from the

chemical

Runoff to sewer may create fire or explosion hazard. This material increases the risk of fire and may aid combustion. Heating may cause a fire. May re-ignite itself after fire

is extinguished. Hazardous decomposition may occur.

Hazardous thermal decomposition

products

Decomposition products may include carbon dioxide, carbon monoxide, nitrogen

oxides, sulfur oxides, metal oxide/oxides.

Special protective equipment for

firefighters

Wear self-contained breathing apparatus and protective suit. Cool containers with flooding quantities of water until well after fire is out. Do not allow run-off from fire-

fighting to enter drains or water courses

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

For non-emergency personal Avoid breathing vapours or mist. Use personal protective equipment as required. Avoid

contact with skin, eyes or clothing.

For emergency responders Use personal protection recommended in Section 8.

Environmental Precautions Do not allow into any sewer, on the ground or into any body of water. If the product

contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations. Prevent further leakage or spillage if safe to do so. Local authorities

should be advised if significant spillages cannot be contained.

Methods and Material for Containment and Cleaning Up

Prevent further leakage of spillage if safe to do so. Dispose of waste product or used containers according to local regulations. Clean with detergents. Avoid solvent cleaners. Dam up. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly. Take up mechanically, placing in appropriate containers for disposal. Contain and collect spillage with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see sections 13).

7. HANDLING AND STORAGE

Precautions for Safe Handling

Protective measuresUse personal protection recommended in Section 8. Never use pressure to empty container.

Comply with the health and safety at work laws. Prevent product from entering drains. Use only with adequate ventilation. Do not breathe dust/fume/gas/vapours/spray. Keep away from clothing and other combustible materials. Keep away from heat, sparks, and open

flame.

Advice on general Occupational hygiene

When using do not eat, drink or smoke. Wash contaminated clothing before reuse. Avoid

contact with skin, eyes or clothing.

Conditions for Safe Storage, Including any Incompatibilities

Keep/store only in original container. Store in accordance with local regulations. Keep unauthorized personnel away. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. To avoid the risk of formation of shock-sensitive crystals or loss of stability, it is important to store the product within the recommended temperature range. Temperature control may be required. Store in segregated and approved area. Protect from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials and food and drink. Store at temperatures not exceeding 25 °C/77 °F. Keep away from heat, sparks and open flame.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control measures

Occupational exposure limits

Chemical Name	CAS#	Exposure Limits
Dibenzoyl peroxide	94-36-0	ACGIH TLV (United States, 3/2019). TWA: 5 mg/m³ 8 hours. NIOSH REL (United States, 10/2016). TWA: 5 mg/m³ 10 hours. OSHA PEL (United States, 5/2018). TWA: 5 mg/m³ 8 hours.
Zinc Stearate	557-05-1	ACGIH TLV (United States, 3/2019). TWA: 10 mg/m³ 8 hours. Form: Inhalable fraction TWA: 3 mg/m³ 8 hours. Form: Respirable fraction NIOSH REL (United States, 10/2016). TWA: 5 mg/m³ 10 hours. Form: Respirable fraction TWA: 10 mg/m³ 10 hours. Form: Total OSHA PEL (United States, 5/2018). TWA: 5 mg/m³ 8 hours. Form: Respirable fraction
Calcium Sulfate	7778-18-9	ACGIH TLV (United States, 3/2019). TWA: 10 mg/m³ 8 hours. Form: Inhalable fraction NIOSH REL (United States, 10/2016). TWA: 5 mg/m³ 10 hours. Form: Respirable fraction TWA: 10 mg/m³ 10 hours. Form: Total OSHA PEL (United States, 5/2018). TWA: 5 mg/m³ 8 hours. Form: Respirable fraction TWA: 15 mg/m³ 8 hours. Form: Total dust

Appropriate Engineering Controls

If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment. Use with adequate ventilation.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels..

Individual Protection Measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection Safety eyewear complying with an approved standard should be used when a risk

assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Hand protection Chemical-resistant, impervious gloves complying with an approved standard should be

worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the

protection time of the gloves cannot be accurately estimated.

Skin and body protection Personal protective equipment for the body should be selected based on the task being

performed and the risks involved and should be approved by a specialist before handling this product. Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

Respiratory Protection Based on the hazard and potential for exposure, select a respirator that meets the

appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important

aspects of use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State paste/solid
Appearance paste/solid
Not determined

Color White

Odor Not determined
Odor Threshold Not determined
pH Not determined
Melting Point Not determined
Boiling Point 100°C (212°F)

Flash Point Closed cup: 94°C (201.2°F) [Pensky-Martens Closed Cup]

Evaporation Rate 0.09 (butyl acetate = 1)
Upper Flammability Limits Not determined

Lower Flammability Limit

Not determined

Not determined

Vapor Pressure 2.3 kPa (17.5 mm Hg) [at 20°C]

Vapor Density 1 [Air = 1]
Relative Density 1.19

10. STABILITY AND REACTIVITY

Reactivity This product, in laboratory testing, neither detonates nor deflagrates and only shows low

or no effect when heated under confinement.

Chemical stability Stable under normal conditions.

Possibility of hazardous_reactions Hazardous reactions or instability may occur under certain conditions of storage or use.

Conditions may include temperature increase, high temperature. Reactions may include

hazardous decomposition, risk of causing fire.

Conditions to Avoid
Avoid all possible sources of ignition (spark or flame). Avoid increased storage

temperature.

Incompatible Materials Reactive or incompatible with combustible materials, reducing materials, copper, iron and

rust

Hazardous decomposition products Under normal conditions of storage and use, hazardous decomposition products should

not be produced.

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Dibenzoyl peroxide	LD50 Oral	Rat	6400 mg/kg	-
Zinc stearate	LD50 Oral	Rat	10 g/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Dibenzoyl peroxide	Eyes – Mild irritant	Rabbit	-	24 hours 500 mg	-
	Skin – Severe irritant	Human	-	1344 hours 5% l	-
	Skin – Moderate irritant	Woman	-	1%	-

Sensitization

Not available

Mutagenicity

Not available

Carcinogenicity

Not available

Classification

<u> </u>			
Product/ingredient name	OSHA	IARC	NTP
Dibenzoyl peroxide	-	3	-

Reproductive toxicity

Not available

Teratogenicity

Not available

Specific target organ toxicity(single exposure)

Not available

Specific target organ toxicity(repeated exposure)

Not available

Aspiration hazard

Not available

Information on Likely Routes of Exposure

Eye Contact: Causes serous eye irritation

Skin Contact: Causes skin irritation. May cause an allergic skin reaction.

Ingestion: No known significant effects or critical hazards. **Inhalation:** No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact: Adverse symptoms may include pain or irritation, watering, redness.

Inhalations: No specific data.

Skin contact: Adverse symptoms may include irritation and redness.

Ingestion: No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

12. ECOLOGICAL INFORMATION

Toxicity

Product/ingredient	Result	Species	Exposure
Calcium Sulfate	Acute EC50 3200000 μg/l Fresh water	Algae - Navicula seminulum	96 hours
	Acute LC50 >1910 mg/l Fresh water	Crustaceans – Ceriodaphnia dubia	48 hours
	Acute LC50 >1970 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 2980000 μg/l Fresh water	Fish - Lepomis macrochirus	96 hours
	Chronic NOEC 360 mg/l Fresh water	Daphnia - Daphnia magna -Neonate	3 weeks
	Chronic NOEC 233 mg/l Fresh water	Fish - Coregonus albula - Egg	60 days

Very toxic to aquatic life

Marine Pollutant - This material meets the definition of a marine pollutant.

Environmental Precautions – Prevent product from entering drains.

Persistence and DegradabilityNo information availableBioaccumulative potentialNo information available

Mobility in soil - No information available

Other adverse effects - No information available

13. DISPOSAL CONSIDERATIONS

Disposal Methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements and all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

14. TRANSPORT INFORMATION

<u>DOT</u>

UN proper Shipping Name
UN proper shipping name UN3108, ORGANIC PEROXIDE TYPE E, SOLID (<52% Dibenzoyl

Peroxide)

Hazard Class 5.2

Packing Group Not applicable

Special Provisions Emergency Response Guide Number - 145

<u>IATA</u>

UN proper Shipping Name UN proper shipping name UN3108, ORGANIC PEROXIDE TYPE E, SOLID (<52% Dibenzoyl

Peroxide)

Hazard Class 5.2

Packing Group Not applicable

Special Provisions A20, A802

IMDG

UN proper Shipping Name UN proper shipping name UN3108, ORGANIC PEROXIDE TYPE E, SOLID (<52% Dibenzoyl

Peroxide)

Hazard Class 5.2

Packing Group Not applicable

Special Provisions 122, 274 EmS-no F-J, S-R

Environmental Hazard Marine pollutant – This material meets the definition of a marine pollutant. Dibenzoyl peroxide,

Zinc Stearate.

Special precautions for user:

Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

15. REGULATORY INFORMATION

U.S. Feral regulations

TSCA

United States inventory (TSCA 8b): All components are active or exempted.

SARA 313

SARA 313 (40 CFR 372.45) supplier notification can be found on the Environmental Data Sheet.

International lists

Canadian DSL All components listed or exempted.

16. OTHER INFORMATION			
HMIS Health Hazards		Flammability	Physical Hazards
	3	0	4

Revision Date May 2022

Revision Notes

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet