



60139 Bonding Putty

PRODUCT INFORMATION:

60139 is a non-flowing, pumpable, polyesters adhesive with improved flow, spread, and hang characteristics. 60139 should be used where a bonding putty is required. It can also be used to radius, fill or for fairing. 60139 excels in its adhesion qualities, fiberglass to fiberglass. 60139 flows very easily, which means lower air pressures can be used at the pump, and MEKP mixes in with ease, and yet, 60139 displays excellent vertical hang properties. 60139 also spreads and feathers smoothly. 60139 does not require flammable labels or segregation in storage as a flammable, because it has been independently tested to be a non-flammable solid. Gel times can be varied for specific needs.

GENERAL PROPERTIES:

Viscosity:	Stable non-flowing paste
Catalyst:	MEK Peroxide
Shelf Life:	6 months (stored out of sun)
Pot Life	22 to 30 minutes with 1% DDM-9 at 76 deg. F
Sp. Gr.:	1.06 to 1.11
Wt/Gallon:	9 pounds
Chemically:	Polyester resin and fillers

USES FOR 60139:

- Power craft
- Sailboats
- Yachts
- Mobile homes
- Travel trailers
- Truck cab
- Automotive
- Most other fiberglass applications

Notice: This information is presented in good faith, but no warranty expressed or implied is given. The information, to our best knowledge, is true and accurate, but all recommendations or suggestions are made without guarantee since the conditions of use are beyond our control.

Revised August 2019